


Accretion



G-12208



Product Information

Description	AC8/15W/R/LED/5CCT	mA	140mA
Color temp	30, 35, 41, 50, 65k	IC Rated	Yes
Output lumens	1000	Dimmable	Triac
Beam angle	120°	OD	8.18"
Input volts	120V	Height	1.00"
Wattage	15W	Warranty	3 Years
CRI	90>	Packed	20

G-12212



Product Information

Description	AC12/24W/R/LED/5CCT	mA	200mA
Color temp	30, 35, 41, 50, 65k	IC Rated	Yes
Output lumens	1750	Dimmable	Triac
Beam angle	120°	OD	11.53"
Input volts	120V	Height	1.00"
Wattage	24W	Warranty	3 Years
CRI	90>	Packed	11.53"10

G-12216



Product Information

Description	AC16/30W/R/LED/5CCT	mA	280mA
Color temp	30, 35, 41, 50, 65k	IC Rated	Yes
Output lumens	2300	Dimmable	Triac
Beam angle	120°	OD	15.63"
Input volts	120V	Height	1.00"
Wattage	30W	Warranty	3 Years
CRI	90>	Packed	6

G-12220**Product Information**

Description	AC20/30W/R/LED/5CCT	mA	370mA
Color temp	30, 35, 41, 50, 65k	IC Rated	Yes
Output lumens	3000	Dimmable	Triac or 0-10V
Beam angle	120°	OD	19.72"
Input volts	120-277V	Height	1.00"
Wattage	30W	Warranty	3 Years
CRI	90>	Packed	5

G-12224**Product Information**

Description	AC24/40W/R/LED/5CCT	mA	370mA
Color temp	30, 35, 41, 50, 65k	IC Rated	Yes
Output lumens	3850	Dimmable	Triac or 0-10V
Beam angle	120°	OD	19.72"
Input volts	120-277V	Height	1.00"
Wattage	40W	Warranty	3 Years
CRI	90>	Packed	5

Accessories**Emergency LED Driver**

25W G-95525
30W G-48411
60W G-95521

**8" Empty Body**

Compatible with G-12208

G-12209
AC8/R/LED/EM/BODY

**8" Emergency Battery**

Compatible with G-12208

G-12210
AC8/15W/R/LED/5CCT/EM

Black Cover

G-12208
Compatible

G-12080
AC8/CV/BK



G-12212
Compatible

G-12000
AC12/CV/BK



G-12216
Compatible

G-12160
AC16/CV/BK



G-12220
Compatible

G-12200
AC20/CV/BK



G-12224
Compatible

G-12240
AC24/CV/BK

Dimensions

