

INSTALLATION INSTRUCTIONS FOR LED CYLINDER

WARNING : These products may represent a possible shock or fire hazard if improperly installed or attached in any way. Products should be installed in accordance with these instructions, current electrical codes or the current National Electric code(NEC).

Electrical Parameters	Model	G-05020 & G-05021 & G-05022 & G-05023 G-05024 & G-05025 & G-05026
	Input	120-277V AC 50/60 HZ
	Output	33-38V DC 450MA
	Lamp Life	50,000 Hours
	Operating Temperature	-40°C to +40°C
	Dimming	Triac or 0-10V Dimming
	Energy used	20 W
	Luminous Flux	1800LM
	Equivalent to:	200W halogen
	CCT Options	27K-30K-35K-40K-50K
	Beam Angle	40 Degree
	CRI	Ra>90
	Approved Location	Damp & Dry Location

Dimmer Compatibility List				
Brand	Family	Model	Load (W)	Max Connected Quantity
LUTRON	Skylark Contour	LECL-153P	150W	1-7
		CTCL-150H	150W	1-7
		LGCL-153PLH	150W	1-7
		CTCL-153P	150W	1-7
		SCL-153P	150W	1-7
	Caseta	S-600P	600W	1-20
		PD-6WCL	600W	1-20
		PD-5NE	150W	1-7
		PD-10NXD	250W	1-10
		DIVA	DVCL-153P	150W
LEVITON	Toggler	TGCL-153P	150W	1-7
	Ariadni	AYCL-153P	150W	1-7
	Maestro	MACL-153M	150W	1-7
	Illumatech	IPL06	150W	1-7
EATON	Smart Dimmer	SureSlide	6672	150W
		AAL06	600W	1-20

Multi Installation Methods When Match with Different Accessories (accessories not included).

