

ACCRETION EM SURFACE MOUNT

G-12210 INSTRUCTIONS



* Item compatible with item G-12208

G-12210 SPECIFICATIONS

Lumens	950	Illumination Time	90 Minutes
Wattage	15	Dimmable	Triac
Volts	120V		



Important Safety Information



- Warning: Risk of Shock.** House electric current can cause painful shock or serious injury unless handled properly. For your safety, always remember to:
A: turn off the power supply at the fuse or circuit breaker box before you install the fixture.
B: Double-check all connections to be sure they are tight and connect.

- This fixture is designed for use in a circuit protected by a fuse or circuit breaker. It is also designed to be installed in accordance with local electrical codes. If you are unsure about your wiring, consult a qualified electrician or local electrical inspector, and check your local electrical code.









- Warning: Risk of Cuts.** Some metal parts in the fixture may have sharp edges. To prevent cuts and scrapes, wear gloves when handling the parts.


- Account for small parts and destroy packing material, as these may be hazardous to children.
- The light source contained in this luminaire shall only be replaced by the manufacturer or his service agent or similar qualified person.
- Terminal block and the suspending accessories is not included. Installation must be performed by qualified person.

Surface Mounted Installation

- Turn off the external power supply. Secure the J-box to the ceiling and ensure enough wiring is exposed for installation.
- Connect the wires (see wiring diagram).
- Attach the emergency power casing to the J-box and tighten securely.
- Mount the bracket onto the emergency power casing using the provided screws.
- Connect the remaining wires using wire caps.
- Push the lamp upward toward the ceiling and rotate it to securely lock the lamp body to the mounting plate. Restore power and confirm the fixture is operating properly.



Wiring Diagram



Caution

- Warning: Risk of fire.**
- Before installing your lighting fixture, thoroughly review enclosed installation manual. If you do not have sufficient electrical wiring experience, please refer to do-it-yourself wiring handbook or have your fixture installed by qualified by a qualified licensed electrician. All electrical connections must be in accordance with local standards. Reliable operating temperature is -20 to +40 degrees.
- Please obey fire prevention regulations, do not cover the fixture with any heat insulated materials.
- Do not change the LED light source or driver inside under any circumstance.