

Jupiter 3.3" Beam Adjustable Cylinder Instruction sheet

WARNING : These products may represent a possible shock or fire hazard if improperly installed or attached in any way. Products should be installed in accordance with these instructions, current electrical codes or the current National Electric code(NEC).

| | | |
|------------------------------|-----------------------|--------------------------------|
| Electrical Parameters | Model | G-33000 & G-33001 |
| | Input | 120-277V AC 50/60 HZ |
| | Output | 33-38V DC 500MA |
| | Lamp Life | 50,000 Hours |
| | Operating Temperature | -40°C to +40°C |
| | Dimming | Triac Dimming or 0-10V Dimming |
| | Energy used | 22W |
| | Luminous Flux | 2000LM |
| | Equivalent to: | 200W halogen |
| | CCT Options | 27K-30K-35K-40K-50K |
| | Beam Angle | 20-55 Degree |
| | CRI | Ra>90 |
| | Approved Location | Damp & Dry Location |

| Dimmer Compatibility List | | | | | |
|---------------------------|-----------------|-------------|-----------|------------------------|-----|
| Brand | Family | Model | Load (W) | Max Connected Quantity | |
| LUTRON | Skylark Contour | LECL-153P | 150W | 1-6 | |
| | | CTCL-150H | 150W | 1-6 | |
| | | LGCL-153PLH | 150W | 1-6 | |
| | | CTCL-153P | 150W | 1-6 | |
| | | SCL-153P | 150W | 1-6 | |
| | | S-600P | 600W | 1-20 | |
| | Caseta | PD-6WCL | 600W | 1-20 | |
| | | PD-5NE | 150W | 1-6 | |
| | | PD-10NXD | 250W | 1-10 | |
| | | DIVA | DVCL-153P | 150W | 1-6 |
| | | Toggler | TGCL-153P | 150W | 1-6 |
| | Ariadni | AYCL-153P | 150W | 1-6 | |
| Maestro | MACL-153M | 150W | 1-6 | | |
| LEVITON | Illumatech | IPL06 | 150W | 1-6 | |
| | SureSlide | 6672 | 150W | 1-6 | |
| EATON | Smart Dimmer | AAL06 | 600W | 1-20 | |

Multi Installation Methods When Match with Different Accessories (accessories not included).

