

# Jupiter 3.7" Beam Adjustable Cylinder Instruction sheet

**WARNING :** These products may represent a possible shock or fire hazard if improperly installed or attached in any way. Products should be installed in accordance with these instructions, current electrical codes or the current National Electric code(NEC).

Electrical Parameters	Model	G-37000 & G-37001
	Input	120-277V AC 50/60 HZ
	Output	33-38V DC 650MA
	Lamp Life	50,000 Hours
	Operating Temperature	-40°C to +40°C
	Dimming	Triac Dimming or 0-10V Dimming
	Energy used	28W
	Luminous Flux	2600LM
	Equivalent to:	300W halogen
	CCT Options	27K-30K-35K-40K-50K
	Beam Angle	20-55 Degree
	CRI	Ra>90
	Approved Location	Damp & Dry Location

Dimmer Compatibility List					
Brand	Family	Model	Load (W)	Max Connected Quantity	
LUTRON	Skylark Contour	LECL-153P	150W	1-5	
		CTCL-150H	150W	1-5	
		LGCL-153PLH	150W	1-5	
		CTCL-153P	150W	1-5	
		SCL-153P	150W	1-5	
		S-600P	600W	1-10	
	Caseta	PD-6WCL	600W	1-10	
		PD-5NE	150W	1-5	
		PD-10NXD	250W	1-8	
		DIVA	DVCL-153P	150W	1-5
		Toggler	TGCL-153P	150W	1-5
		Ariadni	AYCL-153P	150W	1-5
Maestro	MACL-153M	150W	1-5		
LEVITON	Illuminatech	IPL06	150W	1-5	
	SureSlide	6672	150W	1-5	
EATON	Smart Dimmer	AAL06	600W	1-10	

## Multi Installation Methods When Match with Different Accessories (accessories not included).

