



Installation Instructions

1x1, 1x2 SURFACE MOUNT PANEL - 5CCT TEMPERATURE/WATTAGE SELECTABLE



Light fixture 1PCS



13.2x40mm expansion rubber plug 2PCS




ST4.2x30 self-tapping screws 2PCS



4#32 US bolts 2PCS





Wire Nuts 2PCS




Wire Push-in connector 3PCS

NECESSARY TOOLS




1. Shut Off Power

Turn off power at the circuit breaker.




2. Attach Plate

Attach mounting plate (A) to the junction box using screws (D).




3. Secure Plate

Strengthen and fix the mounting plate with expansion rubber plug B and locking screw C. Align orientation as desired.




4. Add Safety Rope

Hang the safety rope on the mounting plate.




5. Thread Wires

Feed junction box wires through the mounting plate (A) hole. Connect fixture wires to junction box wires (black to hot, white to neutral, green to ground). Hook support wire to mounting plate (A).




6. Connect Wires

Connect the bare copper wire to the green ground cable, and connect the other wires in the corresponding color.




7. Set Switches

Switch the color temperature and wattage switches to the desired settings.




8. Align Frame

Position inner aluminum frame edges alongside mounting plate (A) flush to ceiling. Engage lamp body clips into mounting plate (A) mounting points.



9. Engage Fixture

Align the aluminum frame alongside mounting plate (A) flush with the ceiling. Insert bracket into light, engaging shrapnel up to plate (A). Lift and secure light flush to ceiling.



10. Restore Power

Power can now be restored at the circuit breaker. INSTALLATION COMPLETE.