

# Tape Light

## IP65 5.5 Watt Cob

### Product Information

Beam angle	120°
Wattage	5.5 FT / 18W M
CRI	96
Output volts	24V
Dimmable	Yes
Height	2.6mm
Width	10mm
Cut distance	1.97"
Adhesive	3M 9495 300 MP
Roll length	32.80 FT / 10M
Packed	25







### Includes

- 2pc 180° Direct Connector
- 2pc 6" Hard-Wire Starter
- 2pc 4" Jumper Connector

### Product Information

	G-99650	G-99651	G-99652	G-99653	G-99654
Description	T/IP65/COB/5.5W/27K	T/IP65/COB/5.5W/30K	T/IP65/COB/5.5W/35K	T/IP65/COB/5.5W/41K	T/IP65/COB/5.5W/50K
Color temp	2700K	3000K	3500K	4100K	5000K
Temperature	Soft White	Warm White	Neutral White	Cool White	Super White
Lumens	548FT/ 1800 M	565 FT/ 1855 M	651 FT/ 2136 M	635 FT/ 2083 M	609 FT/ 2000 M



## Connectors



**G-9960**  
IP65/C/STS/CONN



**G-99662**  
IP65/C/4"/STS/CONN



**G-99664**  
IP65/C/6"/PTS/CONN




**G-99666**  
MOUNTING CLIP 10PK




**G-99667**  
END CAP 10PK + GLUE

## Channels




**G-96320**  
CH/R/OP/8




**G-96321**  
CH/SM/OP/8

**G-96624**  
CH/SM/5/OP/8/BK


**G-96427**  
CH/SM/5/OP/8/WH




**G-96330**  
CH/SM/.5x.5/OP/8



**G-96316**  
CH/SM/.75/OP/8



**G-96426**  
CH/SM/1/OP/8




**G-96322**  
CH/SM/FLEX/OP/8




**G-96315**  
CH/SM/.5/RD-OP/8




**G-96323**  
CH/SMC/OP/8



**G-96324**  
CH/TL/OP/8



**G-96421**  
1"CH/TL/12'



**G-96422**  
2"CH/TL/12'

## Drivers



G-97608 G-97615 G-97600  
G-97601 G-97602 G-97603

**Mini**  
Electronic  
Driver 24V



G-97620 G-97621 G-97525 G-97622  
G-97612 G-97623 G-97624 G-97625  
G-97626 G-97627

**Multi Dimming**  
Electronic Led  
Driver 24V



G-97526  
G-97527  
G-97528

**Multi Dimming**  
Class 2 Multi Circuit  
Electronic Driver 24V