

LED BR

BR20



BR30



ITEM	G-83384	G-83387
DESCRIPTION	BR20/7/LED/30K	BR20/7/LED/50K
COLOR TEMP	3000K	5000K
OUTPUT LUMEN	550	550
BEAM ANGLE	100°	100°
WATTAGE	7W	7W
EQUIV WATTAGE	50W	50W
CRI	>80	>80
DIMMABLE	YES	YES
MOL (IN/MM)	3.80/97	3.80/97
DIAMETER (IN/MM)	2.5/64	2.5/64
PACK INNER/MASTER	20	20

ITEM	G-83390	G-83393
DESCRIPTION	BR30/11/LED/30K	BR30/11/LED/50K
COLOR TEMP	3000K	5000K
OUTPUT LUMEN	1000	1000
BEAM ANGLE	100°	100°
WATTAGE	11W	11W
EQUIV WATTAGE	75W	75W
CRI	>80	>80
DIMMABLE	YES	YES
MOL (IN/MM)	5.3/134	5.3/134
DIAMETER (IN/MM)	3.7/94	3.7/94
PACK INNER/MASTER	20	20



LED BR

BR40



ITEM	G-83396	G-83399
DESCRIPTION	BR40/17/LED/30K	BR40/17/LED/50K
COLOR TEMP	3000K	5000K
OUTPUT LUMEN	1400	1400
BEAM ANGLE	100°	100°
WATTAGE	17W	17W
EQUIV WATTAGE	120W	120W
CRI	>80	>80
DIMMABLE	YES	YES
MOL (IN/MM)	6.4/163	6.4/163
DIAMETER (IN/MM)	5/126	5/126
PACK INNER/MASTER	20	20

 Dimmable: 5%
  Lifetime: 15 000 hours
  Warranty: 1 years

 CRI 80+ TRUE COLORS
  BEAM ANGLE 100°
  DAMP LOCATION
  UL LISTED
  FCC