




Nebula Linkable Linear



G-21201



Product Information

Description	1 Ft Nebula Linear	mA	100-200mA
Color temp	30, 35, 41, 50, 65K	Output volts	42-54V
Output lumens	600/1200LM	Dimmable	0-10V Dimmable
Input volts	120-277V	Connection type	Direct or BX
Wattage	6/12W	Packed	18
CRI	90>		

G-21202



Product Information

Description	2 Ft Nebula Linear	mA	200-420mA
Color temp	30, 35, 41, 50, 65K	Output volts	42-54V
Output lumens	1200/2400LM	Dimmable	0-10V Dimmable
Input volts	120-277V	Connection type	Direct or BX
Wattage	12/24W	Packed	18
CRI	90>		

G-21203



Product Information

Description	3 Ft Nebula Linear	mA	320-640mA
Color temp	30, 35, 41, 50, 65K	Output volts	42-54V
Output lumens	1800/3600LM	Dimmable	0-10V Dimmable
Input volts	120-277V	Connection type	Direct or BX
Wattage	18/36W	Packed	12
CRI	90>		

G-21204

Product Information

Description	4 Ft Nebula Linear	mA	420-850mA
Color temp	30, 35, 41, 50, 65K	Output volts	42-54V
Output lumens	2400/4800LM	Dimmable	0-10V Dimmable
Input volts	120-277V	Connection type	Direct or BX
Wattage	24/48W	Packed	12
CRI	90>		

G-21205

Product Information

Description	5 Ft Nebula Linear	mA	520-1080mA
Color temp	30, 35, 41, 50, 65K	Output volts	42-54V
Output lumens	3000/6000LM	Dimmable	0-10V Dimmable
Input volts	120-277V	Connection type	Direct or BX
Wattage	30/60W	Packed	12
CRI	90>		

G-21206

Product Information

Description	6 Ft Nebula Linear	mA	640-1280mA
Color temp	30, 35, 41, 50, 65K	Output volts	42-54V
Output lumens	3600/7200LM	Dimmable	0-10V Dimmable
Input volts	120-277V	Connection type	Direct or BX
Wattage	36/72W	Packed	6
CRI	90>		

G-21208

Product Information

Description	8 Ft Nebula Linear	mA	850-1700mA
Color temp	30, 35, 41, 50, 65K	Output volts	42-54V
Output lumens	4800/9600LM	Dimmable	0-10V Dimmable
Input volts	120-277V	Connection type	Direct or BX
Wattage	48/96W	Packed	6
CRI	90>		

G-21210



Product Information

Description	10 Ft Nebula Linear	mA	960-1920mA
Color temp	30, 35, 41, 50, 65K	Output volts	42-54V
Output lumens	6000/10000LM	Dimmable	0-10V Dimmable
Input volts	120-277V	Connection type	Direct or BX
Wattage	60/108W	Packed	6
CRI	90>		

Accessories



2' Power Plug
G-21215



2' Linkable Cord
G-21216



2' Power Cord
G-21217



60" Pendant Kit
G-21218



Bridge Connector
G-21219