

Neptune Backlit Vault Troffer



Selectable Color



CRI 80+ True Colors



Damp Location



120° Beam Angle



Dimmable



Wattage Selectable



Motion Sensor



App Compatible

2' x 2'

G-98240

G-98241 EM



Product Information

Description	F/2X2/50W/BL/VLT/WS3/5CCT	CRI	80>
Description EM	F/2X2/50W/BL/VLT/WS3/5CCT/EM	Dimmable	0-10V Dimmable
Color temp	30, 35, 41, 50, 65K	Dimensions	23.7" X 23.74"
Output lumens	3450/4600/5750	Height	4.92"
Beam angle	120°	Warranty	5 years
Input volts	120/277V	UGR	22
Wattage	30/40/50W	Packed	2

2' x 4'

G-98242

G-98243 EM



Product Information

Description	F/2X4/70W/BL/VLT/WS3/5CCT	CRI	80>
Description EM	F/2X4/70W/BL/VLT/WS3/5CCT/EM	Dimmable	0-10V Dimmable
Color temp	30, 35, 41, 50, 65K	Dimensions	23.74" X 47.72"
Output lumens	5750/6900/8050	Height	4.92"
Beam angle	120°	Warranty	5 years
Input volts	120/277V	UGR	22
Wattage	50/60/70W	Packed	1

Accessories




Surface Kit
For 2x2 troffer use G-90222
For 2x4 troffer use G-98224



Flange Kit
For 2x2 troffer use G-48305
For 2x4 troffer use G-48307



Smart Motion Sensor
G-98210



Motion Sensor
G-98211




Controller
G-98212

Dimensions

G-98240

G-98241 EM



G-98242

G-98243 EM

