

TAPE LIGHT

RGBWW COB

G-48525
G-48526



REMOTE G-99722



CONTROLLER G-99723



AMPLIFIER G-99733



- SOFT WHITE 2700K
- WARM WHITE 3000K
- NEUTRAL WHITE 3500K
- COOL WHITE 4100K
- SUPER WHITE 5000K
- DAYLIGHT 6500K

16.4FT

ITEM	G-48525		
DESCRIPTION	TP/COB/21W/RGBWW	WIDTH	12 mm
VOLTAGE	24V DC	HEIGHT	1.8 mm
WATTAGE	6.4W - FT. / 21W - M.	CUTTABLE	1.64"
OUTPUT LUMEN	365 - FT. / 1200 - M.	CRI	90>
BEAM ANGLE	120°	ADHESIVE	3M 9495 300 MP
DIMMABLE	Yes	ROLL LENGTH	16.4FT / 5M.
COLOR TEMP	RGBWW + 27-65k	PRE SOLDERED	YES

100FT

ITEM	G-48526		
DESCRIPTION	TP/COB/21W/RGBWW/100FT	WIDTH	12 mm
VOLTAGE	24V DC	HEIGHT	1.8 mm
WATTAGE	5.5W - FT. / 18W - M.	CUTTABLE	1.64"
OUTPUT LUMEN	365 - FT. / 1200 - M.	CRI	90>
BEAM ANGLE	120°	ADHESIVE	3M 9495 300 MP
DIMMABLE	Yes	ROLL LENGTH	100FT / 30.5M
COLOR TEMP	RGBWW + 27-65k	PRE SOLDERED	YES

RGBWW COB Tape Light features uniform illumination without the need for additional diffused covers or accessories. Featuring a premium seamless line of light.

- Seamless COB design that eliminates virtually all LED dotting
- A continuous band of flawless light output with no pixelated hot spots-even without a lens
- Low heat generation, Channel not required for sink
- Double end impute power connection option
- 50,000 hours rated life

Accessories

Starter Connector



G-49527

Strip to Strip Connector



G-49528

Wire Jumper/Connector



G-49529



Warranty:
3 years



Dimmable:
5%



Inner/Master
25/100



Double end
Connector



SELECTABLE
COLOR TEMPERATURE



CRI 90+
TRUE COLORS



BEAM
ANGLE
120°



IP 20



INDOOR
USE



UL
LISTED