

Venus Regress



Selectable Color



CRI 90+ True Colors



Wet Location



Air Tight



60° Beam Angle



Dimmable



IC Rated 23W Only



Wattage Selectable

Product Information

Color temp	27, 30, 35, 41, 50k	Dimmable	Triac or 0-10V Dimming
Output lumens	2000/2600/3500	Cut out	5.00"
Beam angle	60°	OD	5.71"
Input volts	120/277V	Height	2.70"
Wattage	40W/30W/23W	Wire space	14sq Inches
CRI	90>	Warranty	3 years
mA	980/750/550mA	Plate	G-98800 8 Punch Out
Output volts	38V		G-98810 8 Punch Out
IC rated	Only at 23W	Packed	18

Product Information

Color temp	27, 30, 35, 41, 50k	Dimmable	Triac Or 0-10V Dimming
Output lumens	2000/2600/3500	Cut out	5.00"
Beam angle	60°	OD	5.71"
Input volts	120/277V	Height	2.70"
Wattage	40W/30W/23W	Wire space	14sq Inches
CRI	90>	Warranty	3 years
mA	980/750/550mA	Plate	G-98800 8 Punch Out
Output volts	38V		G-98810 8 Punch Out
IC rated	Only at 23W	Packed	18

G-20216

R5/40W/WS3/R/LED/SCCT

White

G-20195

R5/40W/WS3/R/LED/B/SCCT

Black

G-20218

R5/40W/WS3/SQ/LED/SCCT

White

G-20196

R5/40W/WS3/SQ/LED/B/SCCT

Black

Accessories



Emergency LED Driver
25W G-95525
30W G-48411
60W G-95521



Multi Driver Converter
22W G-95826



Extension Cords
5ft G-20247
10ft G-20248
20ft G-19822
30ft G-19823

Note: Emergency batteries must equal or exceed the fixture's maximum wattage. Keep in mind that these fixtures feature selectable wattage.

Dimensions

